

## **TEST REPORT**

## SINTEF NBL as

Address: NO-7465 Trondheim, Norway

Location: Tillerbruvegen 202

Telephone: +47 73 59 10 78 Fax: +47 73 59 10 44 E-mail: nbl@nbl. sintef.no Internet: nbl.sintef.no

Enterprise No.: NO 982 930 057 MVA

Prevent Systems AS
Fire Extinguishing Tests according to:
IMO Res.265(84) –Public Space.
Conducted November 2009

AUTHOR/PROJECT MANAGER

Christian Sesseng

CLIENT(S)

TITLE

Prevent Systems AS Fåberggaten 126 2615 Lillehammer

| REPORT NO.                        | CLASSIFICATION | CLIENTS REF.                                        |                         |
|-----------------------------------|----------------|-----------------------------------------------------|-------------------------|
| NBL 107492-A                      | Restricted     | Erling Mengshoel                                    |                         |
| CLASS. THIS PAGE                  |                | PROJECT NO.                                         | NO. OF PAGES/APPENDICES |
| Restricted                        |                | 107492                                              | 63                      |
| ELECTRONIC FILE CODE              |                | CHECKED BY (NAME, SIGN.)                            |                         |
| Report_Prevent_Systems_IMO265.pdf |                | Are W. Brandt / / / / / / / / / / / / / / / / / / / |                         |
| FILE CODE                         | DATE           | APPROVED BY (NAME, POSITION, SIGN.) Autlos Asstad   |                         |
| -                                 | 2010-01-04     | Atle W. Heskestad, Director                         |                         |

## ABSTRACT

This report presents results from fire extinguishing tests conducted with water mist system delivered by Prevent Systems AS according to IMO MSC/Circ. 265, chapter 6 - "Public Space Fire Tests".

The nozzle type, hereby denoted Type 2, delivered by Prevent Systems, was used for the tests. The nozzles were tested with 4.0 m spacing. The k-factor was measured to be 13.44  $^{kg}/_{min\cdot bar}$ . The tests were conducted in two rounds. The first round with a 2.5 m ceiling height and the second round with a 5.0 m ceiling height.

Eight tests of relevance to the acceptance of the system according to the requirements for "Public Space" are presented in this report.

All reported tests satisfy the requirements of the test method.

| KEYWORDS           | ENGLISH        | NORWEGIAN |  |
|--------------------|----------------|-----------|--|
| GROUP 1            | Fire           | Brann     |  |
| GROUP 2            | Extinguishment | Slokking  |  |
| SELECTED BY AUTHOR | Water Mist     | Vanntåke  |  |
|                    | Tests          | Forsøk    |  |